# MAINTENANCE AND SERVICE

## CP7160 / CP7165 **Airhammer Kits**

- Robust chisel hammers with built-in air suspension (reduces
- Quick change chuck foreasy
- change of Chisel included
- Contains:
- Tool (CP7160 or CP7165)
- A quick change retainer - A spring retainer
- A mini oiler - A Chicago Pneumatic soft bag



2450:-

2600:-Art.-Nr.: 8941071601 Art.-Nr.: 8941071651



# Air reciprocating saw

- Premium tool for all cutting applications
- Low Vibrations
- Great power and speed of 10,000 strokes per minute
- Stroke: 10mm
- 360° swivel air inlet
- Net weigth: 0,86kg



Art.-Nr.: 8941079011

CP7165K

## **CP9792C** Keyless Drill

- 10 mm Chuck
- High ergonomiccomfort and optimal control
- User-friendly
- Speed: 2100 rpm

6 mm and 1/4»

Air die grinder

 Torque: 5 1/2 Nm High quality industrial Jacobs®

**CP74 SERIES** 

drill chuck

• Right/left rotation



1499:-Art.-Nr.: 8941097920

## CP72XXCVE

Orbital Palm Sanders, 2.5-10mm

- Powerful and easy to use for vertical and horizontal applications
- Shut-off and speed control switch
- 3 variations for different applications:
- CP7225CVE: 8941272253, 2.5 mm: used for final sanding
- CP7255CVE: 8941272553, 5 mm: great for surface preparation
- CP7215CVE: 8941272153, 10 mm: great for heavy material removal



2100:-For all CP72XXCVE













Watch the video on YouTube



1340: 1499:- 1499:- 1390:- 2195:- 3850:-

SEE THE CP74 SERIES IN ACTION!





J			•			
Modell	CP7405	CP7406	CP7408	CP7410	CP7411	CP7412
Article no.	8941074050	8941074060	8941074080	8941074100	8941074110	8941074120
Collet size	1/4" and 6 mm	1/4" and 6 mm				
Power	250 W	250 W				
Free speed	28.000 Rpm	23.000 Rpm	23.000 Rpm	27.000 Rpm	22.000 Rpm	22.000 Rpm
Weight	0,5 kg	0,6 kg	0,62 kg	0,65 kg	0,7 kg	1,1 kg
Air requirement at maximum speed	1,3 [l/s]/ 9 [Nl/s]	1,7 [l/s]/ 12,1 [Nl/s]	1,7 [l/s]/ 12,1 [Nl/s]			
Minimum hose size	10 mm	10 mm				
Size air inlet thread	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"
Sound pressure	76,2 dB(A)	78,1 dB(A)	78,6 dB(A)	76,1 dB(A)	80,7 dB(A)	80,4 dB(A)
Sound power	87,2 dB(A)	89,1 dB(A)	89,6 dB(A)	87,1 dB(A)	91,7 dB(A)	91,4 dB(A)
Vibrations [m/s² - k]	3,60 - k = 0,98	5,40 - k = 1,27	4,30 - k = 0,93	4,90 - k = 0,96	3,10 - k = 0,79	2,60 - k = 0,76



At Chicago Pneumatic, we have a passion for performance and long-lasting partnerships. Since 1901, we have been committed to reliability based on technology and trust.

People: Passion. Performance.

# **CORDLESS TOOLS**

# **COMFORT. ERGONOMICS. POWER.**



## Cordless Impact Wrench 1/2"

- The performance of a Twin-hammer with the advantages of an advanced electric motor
- Offers high flexibility and protects against arm
- No more over tightening the bolts thanks a torque CAMPAIGN PRICE cut-off when tightening

Non-binding price recommendations. All prices are in euros plus VAT.

find other specialist dealers on our website: www.cp.com/nordic.

Promotion valid from 04/01/2021 - 12/31/2021

Västgötavägen 30 | 45134 Uddevalla | Sweden

2-stage tightening

Chicago Pneumatic

10350:-Art.-Nr.: 8941088540



- Lightweight construction thanks to the compact CP battery
- 250 cycles before changing the battery
- Powerful torque thanks to special gears
- The gearbox of the CP86 allows high-precision tightening with constant repeatability
- Intuitive large OLED display

**INTERESTED?** ASK US FOR A QOUTE!

Model	CP8854	Model
Article no.	8941088540	Article no.
quare drive	1/2"	Square dri
lax Torque (Reverse)	1.050 Nm	Max Torqu
attery pack	Lithium-ion	Battery pa
oise level	91 db(A)	Noise leve
et weight	2,5 kg + 0,49 kg Battery	Net weigh
/ibration	1,5 m/s <sup>2</sup>	Vibration

CP8613 6151570000 3/4" ie (Reverse) 1.300 Nm Li ion, 36V, 2,5 Ah < 72 db(A) 4,5 kg + 0,8 kg Battery < 2.5 m/s<sup>2</sup>

For orders and deliveries contact your preferred Specialist dealers, you can also

You want to be regularly informed about new products and events? Sign up to our CP email newsletter at: www.cp.com/en/tools/expert-corner/subscribe


Changes, errors and misprints reserved.





# 1/2" Impact

# Wrench



 Weighing just 2.25 kg, the CP7741 impact wrench (short spindle) is 15 percent lighter than the previous model and

is therefore even easier to

 The composite housing offers optimal ease of use with significantly less heat transfer between the motor and the

> 1750:-Art.-Nr.: 8941077410


he entry-level

**PRODUCT** 

HIGHLIGHT

# Our complete assortment online:






- CP accessories
- Technical documentation CP sales and dealer contacts







TIRE SERVICE



Modell	CP7755	CP7748	CP7748-2	CP7748TL
Article no.	8941077550	8941077481	8941077486	8941077487
Square drive	1/2"	1/:	2""	1/2"
Max Torque (Reverse)	1.300 Nm	1.30	0 Nm	1.300 Nm
Working torque range (forward)	80 - 575 Nm	95 - 7	50 Nm	90 - 140 Nm
Free speed	7.700 rpm	7.000	) rpm	7.000 rpm
Average air consumption	1,8 l/s	3	l/s	3 l/s
Clutch Type	Twin-Hammer	Twin-H	ammer	Twin-Hammer
Air Inlet Thread Size	1/4"	1/	4"	1/4"
Noise level	94 dB(A)	94,3	dB(A)	94.3 dB(A)
Net weight	1,85 kg	2 kg	2,11 kg	2 kg
Vibration	8.5 m/s <sup>2</sup>	12 m/s <sup>2</sup>	11.3 m/s <sup>2</sup>	12 m/s <sup>2</sup>

# **CP8915**

## 1/2" Torque Wrench, 40-200 Nm

- · Ideal for cars, motorcycles, guads and for engine and transmission maintenance
- Accuracy: 4% according to EN ISO 6789:2003
- Torque: 40-200Nm
- Length: 495mm Weight: 1.57kg

1.870:-



# 1/2" Torque Wrench, 60-340 Nm

- Ideal for cars, motorcycles, guads and for
- Accuracy: 4% according to EN ISO 6789:2003



## **Our 1/2" Recommendation** For tight workspaces

3					<u> </u>
Modell	CP7732C	CP7749	CP7749-2	CP7829H	CP7829
Article no.	8941077321	8941077491	8941077493	8941078294	8941078293
Square drive	1/2"		1/2"	1/2"	3/8"
Max Torque (Reverse)	625 Nm	13	300 Nm	95	5 Nm
Working torque range (forward)	70 - 387 Nm	135	- 704 Nm	15 -	68 Nm
Free speed	9.410 rpm	7.0	000 rpm	225	5 rpm
Average air consumption	2,6 l/s		3 l/s	5,	2 l/s
Clutch Type	Jumbo	J	lumbo	Ju	mbo
Air Inlet Thread Size	1/4"		1/4"	1	/4"
Noise level	95,5 dB(A)	93 dB(A)	95 dB(A)	93	dB(A)
Net weight	1 kg	1,8 kg	2 kg	1,	2 kg
Vibration	10,8 m/s <sup>2</sup>	10	),9 m/s²	10,3	3 m/s <sup>2</sup>





5600:-

Art.-Nr.: 8941077691





7300:-

7300:-Art.-Nr.: 8941077827

CP7763	CP7769	CP7779	CP7782	CP7782TL-6
8941077630	8941077691	8941077791	8941077820	8941077827
3/4"	3/4"	1"	1"	1"
1.630 Nm	1.95	0 Nm	2.600 Nm	2.600 Nm
136 - 1288 N.m	407 - 1.	464 Nm	500 - 2.000 Nm	400 - 440 Nm
6.300 rpm	6.50	0 rpm	5.200 rpm	5.200 rpm
3.5 l/s	4,8 l/s		4,8 l/s	4,8 l/s
Twin-Hammer	Twin-Hammer		Twin-Hammer	Twin-Hammer
3/8 "	3/	/8"	1/2"	1/2"
96 dB(A)	96,8	dB(A)	100 dB(A)	100 dB(A)
5.25 kg	3,1	5 kg	10.1 kg	11,6 kg
10.4 m/s²	12,97	7 m/s²	7,8 m/s <sup>2</sup>	7,8 m/s²

# 3/4" Torque Wrench, 150-750 Nm

- Ideal for small and medium-sized trucks
- Accuracy: 4% according to EN ISO 6789:2003 • Torque: 150-750 Nm

- Length: 610mm

# Length: 1,060 cm Weight: 16.2 kg 6750:-Art.-Nr.: 8941089200

# ACCURATE ERGONOMIC.

- 1" Torque Wrench, 200-1.000 Nm
- Ideal for large trucks, buses, construction machinery and agriculture
- Accuracy: 4% according to EN ISO 6789:2003 • Torque: 200-1,000 Nm
- Length: 1,255mm Weight: 16.2 kg

8350:-

## **CP Socket sets**



Large selection, available as a

For 3/8», 1/2», 3/4», 1», from 7 to 70 mm.

SS414WP 1/2" Socket set Kit of 4: 17, 19, 21 & 22mm.

SS4114D 1/2" Socket set

SS814D 3/4" Socket set

SS413DTW 1/2" Socket set

Kit of 3: 17, 19 & 21mm.

Art.-Nr.: 8940166760

SS618D 3/4" Socket set

Art.-Nr.: 8940164473

Kit of 8: 26,27,29,30,32,35,36 & 38 mm

You can find more information in our accessories catalogue: http://qr.cp.com/sockets-brochure

For your tools

tools is key to ensure productivity, meet clients' demands and operators' safety.

Art.-Nr.: 8940176598



# **CP800-Series**

# Trolley Jacks, 1.5t, 2t & 3t

- · Low profile and high load capacity
- 1,5,2 and 3 tons lifting capacity
- Lifting height up to 505 mm
- · Welded steel chassis with reinforced edges
- Hand pump and foot pedal for quick approach without load
- Handle with protective pad and soft rubber pad on saddle plate
- Easy release of the load by turning handle

· Large base plate for good standing and stability

• Double guide and chrome-plated steel piston in

· Automatically welded construction for 100% tight-

• Thread extension in the piston for fast and easy

ness, robustness and easy disassembly

Safety valve to protect against overload

one piece, resulting in maximum load capacity and

Low profile construction

CP81120

durability

Bottle Jack 12 t

height adjustment

1190:-

Art.-Nr.: 8941181120



3900:-Art.-Nr.: 8941181015


3990:-Art.-Nr.: 8941181020

4100:-

Art.-Nr.: 8941181030

## **CP820-Series** Jack Stands 2t, 3t, 6t

- Support stand made of ductile iron and robust
- · Extra large footplates
- Positions in height: 10



# steel skeleton construction

- Delivery in pairs



/lodel	CP82020	CP82030	CP82060
Article no.	8941082020	8941082030	8941082060
Capacity	2t	3t	6t
/lax Height	425 mm	455 mm	620 mm
/lin Height	280 mm	300 mm	400 mm
let Weight	2,5 kg	3 kg	5 kg
Price	399:-	499:-	950:-

# CP85031 Air-hydraulic Jack, 30 t

- High Lifting
- Air powered piston
- for transport
  - Anti dust seals for high durability
  - Convenient joystick controls
  - Cylinder mounted carrying handle
  - 1.3 m / long handle bar (1 piece handle) allows easy access to controls when fully positioned under vehicle

  - · Maximum height: 772 mm at 30 tons





## **CP Workshop Presses** 20t-100t pressing power

- 2 holes in each foot to fix in the floor
- Steel frame
- 2 step stroke system
- Large gauge measuring short and metric tons
- Delivered with 2 V blocks
- Easy to use handle with rubber grip
- Delivered with a quick chuck and 8 punches



You want to be regularly informed

about new products and events?

www.cp.com/en/tools/expert-corner/subscribe

Sign up to our CP email newsletter at:

 16m hose BSP thread

HR8113

Hose Reel

13mm inner diameter

**WORKSHOP EQUIPMENT** 

- Weight 10.7 kg
- Air connection 1/2"





# **CP FRL Unit:**

## Take control of your operating costs


Extends the life of your air tools and reduces the energy demand. Tools are automatically set to the optimum oil supply is controlled and the filter provides protection against dirt and water

## CLEAN AIR, **FULL POWÉR.**

FRL Unit- 1/2" Connection BSP











Online Catalog Pneumatic Tools Online workshop equipment catalogu



Technical documentation









- engine and transmission maintenance
- Torque: 60-340 Nm
- Weight: 1.76kg







# SS413WP 1/2" Socket set Kit of 3: 17, 19 & 21mm.

set or individually. imperial and metric, short and standard.

Art.-Nr.: 8940164459

Kit of 14: 10-19,21,22,26&27 mm Kit of 4: 27, 32, 33 & 36 mm Art.-Nr.: 8940166016



# Lubrication

**Protection and Care** 


The appropriate care of pneumatic

CPA1015 Air Tool Oil 125ml

**Grease Gun** Art.-Nr.: C098689







- Handle bar locks in 3 positions: 45°, 90° & 180°
- Large & soft rubber wheels

